

# Victory® XL 130

OUTSTANDING OUTDOOR  
PERFORMANCE WITH  
LUXURIOUS FEATURES

## VICTORY® XL 130

The **Victory® XL 130** features a powerful drivetrain and large 13" wheels to handle rugged outdoor terrain. Luxury touches like a wraparound delta tiller, low-profile non-marking tyres and an LED light blend seamlessly give the Victory XL 130 a sleek, sporty style.



# Victory® XL 130

Model number:	SC713
Weight capacity:	158.75 kg
Maximum speed <sup>1</sup> :	Up to 15 km/h
Ground clearance <sup>2</sup> :	9.69 cm
Turning radius:	170 cm
Overall length <sup>2</sup> :	136 cm
Overall width <sup>2</sup> :	63.65 cm
Front tyres:	10 cm x 33 cm
Rear tyres:	10 cm x 33 cm
Seat-to-deck:	46 cm
Seat-to-ground:	63 cm – 67 cm
Suspension:	Front & Rear
Range per charge <sup>1,4</sup> :	Up to 42.7 km (with 55 AH batteries)
Maximum obstacle climbing ability:	5 cm
Total weight without batteries:	65.28 kg
Heaviest piece when disassembled:	34 kg (rear section)
Standard seating:	Type: Reclining high-back seat with headrest Weight: 23 kg Material: Black Vinyl Dimensions: width – 45 cm (overall width) depth – 48 cm (effective depth)
Drive system:	Rear-wheel drive, sealed transaxle, 24-volt DC motor
Dual braking system:	Regenerative and electromechanical
Battery requirements <sup>3</sup> :	Two 12-volt, deep cycle Size: NF-22 (55AH) (standard) Group 24 (70AH) (optional) Weight: <b>NF-22:</b> 17.16 kg each <b>Group 24:</b> 24.27 kg each
Battery charger:	5-amp, off-board (w/ 55 amp batteries)/ 8-amp off-board (w/ 70 amp batteries)

Colors:



Candy  
Apple Red



Mercury  
Silver



Black

## Features

- Large 33 cm pneumatic tyres for excellent outdoor performance
- Full lighting package including directional signals and angle-adjustable, LED headlight
- Delta tiller with wraparound handles
- Front basket standard
- Easily accessible tie down points (for transport of unoccupied scooter)
- Rearview mirror standard

## Options

- Rear basket
- Double crutch holder
- Additional rearview mirror
- Oxygen tank holder

<sup>1</sup> Varies with user weight, terrain type, battery amp-hour (AH), battery charge, battery condition and tyre condition.

<sup>2</sup> Due to manufacturing tolerances and continual product improvement, this specification can be subject to a variance of (+ or – 3%).

<sup>3</sup> AGM or gel cell type required.

<sup>4</sup> Tested in accordance with ANSI/RESNA, WC Vol2, section 4 & ISO 7176-4 standards. Results derived from theoretical calculations based on battery specifications and drive system performance test conducted at maximum weight capacity.

NOTE: All specifications subject to change without notice.

The information contained herein is correct at the time of publication; due to Pride's commitment to constant improvement and development, we reserve the right to alter specifications without prior notice.

Theoretical range is calculated under test conditions in accordance with European standards. Actual range in normal use will depend on many factors, including the condition of the vehicle and its batteries, the weight of the driver, correct tyre pressures, ambient temperature, and the gradient and surface of the road or pavement.